

SYSMEX SAS-100 WRIGHT STAIN SOLUTION & BUFFER SOLUTION

Material Safety Data Sheet

Wright Stain Solution
Wright Buffer Solution
Manufactured by:
Richard-Allan Scientific
4481 Campus Drive
Kalamazoo, MI 49008
(800) 522-7270
8.00 a.m. - 5.00 p.m. EST

Wright Buffer Solution
Distributed by:

Sysmex America, Inc.
One Nelson C. White Parkway
Mundelein, IL 60060

Emergency Contact

CHEMTREC (800) 424-9300
24 hours Everyday

1. SUBSTANCE IDENTIFICATION

SUBSTANCE: SYSMEX SAS-100 WRIGHT STAIN

CATALOG NUMBER: 161-6001-0, 161-6002-0

SUBSTANCE: SYSMEX SAS-100 BUFFER SOLUTION (7.15pH)

CATALOG NUMBER: 161-6003-0, 161-6004-0

SUBSTANCE: SYSMEX SAS-100 BUFFER SOLUTION (6.8 pH)

CATALOG NUMBER: 161-6005-0, 161-6006-0

2. COMPOSITION AND INGREDIENTS INFORMATION

Stain Solution

Methanol CAS# 67-56-1 99%

Wright Stain CAS# 68988-92-1 1%

Buffer Solutions

Phosphate Salts 1%

3. HAZARDOUS IDENTIFICATION:

Wright Stain:

NFPA RATINGS (SCALE 0-4) HEALTH = 1 FIRE = 3 REACTIVITY = 0

Emergency Overview: DANGER: FLAMMABLE, POISON, IRRITANT

Methanol, a colorless, flammable, poisonous liquid with a slight alcohol odor. Methanol is an experimental teratogen with experimental reproductive effects. Vapor is harmful, may be fatal or cause blindness if swallowed, it cannot be made nonpoisonous, harmful if inhaled, causes irritation to eyes, skin and respiratory tract.

Primary Routes of Exposure: Inhalation, ingestion, skin and eye contact.

Acute Effects: Irritation of eyes, nose, throat and mucous membranes of the upper respiratory tract. Breathing of vapor or absorption through skin can cause permanent blindness. Exposure to high concentrations can cause headaches, nausea, vomiting, dizziness, unconsciousness or death.

Chronic Effects: Irritation of the eyes, nose, throat and mucus membranes of the upper respiratory tract. Repeated exposure can cause dryness, irritation, inflammation of the skin, visual impairment with symptoms ranging from mild blurring to contraction of visual fields to sometimes complete blindness. Long term effect may include liver damage.

Potential Health Effects:

Inhalation: May cause irritation of mucous membranes and respiratory tract.

Eye Contact: Vapor may cause eye irritation.

Skin Contact: Contact with liquid could cause irritation, dryness and cracking of the skin. Contact with stain component will cause staining of the skin.

Ingestion: May cause nausea, vomiting, dizziness, blindness or death.

Buffer Solutions:

Emergency Overview: Contains no hazardous materials. Buffer is comprised of phosphate salts and non-active ingredients.

4. FIRST AID PROCEDURES:

Wright Stain:

Inhalation: Remove from exposure area to fresh air immediately. If breathing has stopped, give artificial respiration. If breathing is difficult give oxygen. Get medical attention immediately.

Eye Contact: Flush eyes immediately with large amounts of water, occasionally lifting upper and lower lids for at least 15-20 minutes. If irritation persists, seek medical attention.

Skin Contact: Remove contaminated clothing and shoes immediately. Wash effected area with soap or mild detergent and large amounts of water. If irritation persists, seek medical attention.

Ingestion: if swallowed, induce vomiting by giving two glasses of water and sticking fingers down throat. Keep victim's head lower than hips to prevent aspiration into lungs. Never give anything by mouth to an unconscious person. Call a physician immediately.

ANTIDOTE: Give ethanol, 50% (100 proof), 1.5 mL/Kg orally initially, diluted to no more than 5% solution, followed by 0.5-1.0 mL/Kg every 2 hours orally or intravenously for 4 days in order to reduce metabolism of methanol and to allow time for its excretion. Blood ethanol level should be in the range of 1-1.5 mg/mL (Dreisbach, Handbook of Poisoning, 12th ed.). Antidote should be administered by qualified medical personnel.

Buffer Solutions:

Wash affected area with copious amounts of water for at least 15 minutes. If ingested, contact a physician.

5. FIRE FIGHTING PROCEDURES

FIRE AND EXPLOSION HAZARD: DANGEROUS FIRE HAZARD AND MODERATE EXPLOSION HAZARD WHEN EXPOSED TO HEAT, FLAME, OR OXIDIZERS. VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. VAPOR-AIR MIXTURE IS EXPLOSIVE.

FLASH POINT: 54°F (12°C) (CC) Methanol

LOWER EXPLOSIVE LIMITS: 6.0%

UPPER EXPLOSIVE LIMIT: 36.0%

AUTOIGNITION TEMP: 752°F (385°C)

FIRE FIGHTING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, WATER SPRAY OR ALCOHOL-RESISTANT FOAM (1993 Emergency Response Guidebook, DOT P 5800.5). FOR LARGER FIRES USE WATER SPRAY, FOG, OR ALCOHOL - RESISTANT FOAM (1993 Emergency Response Guidebook), DOT P 5800.5).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers may explode in fire, methanol burns with a non-luminous blue flame. Vapors are heavy and will travel long distances back to a source of ignition. **POISONOUS GASES ARE PRODUCED IN THE FIRE. CONTAINERS MAY EXPLODE IN FIRE.**

6. ACCIDENT RELEASE MEASURES:

SMALL OR LARGE SPILL: Shut off ignition sources. Do not touch spill material. Stop leak if you can do it without risk. Take up spilled material with sand or other absorbent material and place into containers for later disposal. No smoking, flames or flares in hazard area! Keep unnecessary people away

REPORTABLE QUANTITY (RQ): 5000 POUNDS

The Superfund Amendments and Reauthorization Act (SARA) Section 304 requires that a release equal to or greater than the reportable quantity for this substance be immediately reported to the local emergency planning committee and the state emergency response commission (40 CFR 355.40). If the release of this substance is reportable under CERCLA Section 103, the National Response Center must be notified immediately at (800) 424-8882 or (202) 426-2675 in the metropolitan Washington, D. C. area (40 CFR 302.6).

7. HANDLING AND STORAGE:

GENERAL HANDLING: Keep away from heat, sparks and flame. Keep pack box in an upright position to prevent leakage. Avoid breathing vapor or spray mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling. In case of spillage, absorb and wash with large volumes of water immediately.

OBSERVE ALL FEDERAL, STATE AND LOCAL REGULATIONS WHEN STORING OR DISPOSING OF THIS SUBSTANCE. FOR ASSISTANCE, CONTACT THE DISTRICT DIRECTOR OF THE ENVIRONMENTAL PROTECTION AGENCY. STORE IN ACCORDANCE WITH 29 CFR 1910.106. STORE AWAY FROM INCOMPATIBLE SUBSTANCES.

Methanol is a class 1B flammable liquid (NFPA). Follow the maximum allowed pile heights specified in the BOCA codes or the NFPA manual. Local fire authority should be notified for storage of this material in any quantity. Local permits are required for storage in warehouse quantities.

Store at 15°C to 30°C (59°F to 86°F) in a well ventilated place, away from sources of ignition. In laboratory quantities, store away from oxidizing material, mineral acids, and chloroform. Store Methyl Alcohol in areas equipped with automatic sprinklers or fire extinguishing system. Containers of this material may be hazardous when empty. Since emptied containers retain product residues, assume emptied containers to have the same hazard qualities as full containers.

8. EXPOSURE CONTROL (PERSONNEL PROTECTION)

VENTILATION:

Provide local exhaust or process enclosure ventilation to meet the published exposure limits. Ventilation equipment must be explosion-proof.

RESPIRATORY PROTECTION:

Where the potential exists for exposures over 200 ppm, use a NIOSH approved respirator with an organic vapor cartridge/canister. More protection is provided by a full facepiece respirator than by a half-mask respirator, and even greater protection is provided by a powered-air purifying respirator.

FOR FIRE FIGHTING AND OTHER IMMEDIATELY DANGEROUS TO LIFE OR HEALTH CONDITIONS: Any self-contained breathing apparatus that has a full face piece and is operated in a pressure-demand or other positive-pressure mode. Any supplied-air respirator that has a full face piece and is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode.

CLOTHING:

Employee must wear appropriate protective (impervious) clothing and equipment to prevent repeated or prolonged skin contact with this substance.

GLOVES:

Employee must wear appropriate protective gloves to prevent contact with this substance. ACGIH recommends NITRILE rubber or VITON as good to excellent protective materials.

EYE PROTECTION:

Employee must wear splash-proof or dust-resistant goggles to prevent eye contact with this substance.

EMERGENCY EYE WASH:

Where there is any possibility that an employee's eyes may be exposed to this substance, the employer should provide an eye wash fountain within the immediate work area for emergency use. Eye wash stations must, at a minimum, provide a full 15 minutes of flushing.

EXPOSURE LIMITS:

100% Methyl Alcohol (Methanol):

200 ppm (260 mg/m³) OSHA TWA (SKIN); 250 ppm (310 mg/m³) OSHA STEL

200 ppm (262 mg/m³) ACGIH TWA (SKIN); 250 ppm (328 mg/m³) ACGIH STEL

200 ppm (260 mg/m³) NIOSH RECOMMENDED TWA (SKIN);

250 ppm (325 mg/m³) NIOSH RECOMMENDED STEL

200 ppm (260 mg/m³) DFG MAK TWA (SKIN);

400 ppm (524 mg/m³) DFG MAK 30 MINUTE PEAK, AVERAGE VALUE, 4 TIMES/SHIFT

MEASUREMENT METHOD: SILICA GEL TUBE; WATER; GAS CHROMATOGRAPHY WITH FLAME IONIZATION DETECTION; (NIOSH VOL. III #2000, METHANOL).

9. PHYSICAL AND CHEMICAL PROPERTIES

Wright Stain:

DESCRIPTION: Dark blue/purple liquid with a characteristic odor.
BOILING POINT: 149°F (65°C)
SPECIFIC GRAVITY: 0.7914
EVAPORATE RATE: (butyl acetate): 4.6
VISCOSITY: 0.59 CPS @ 20°C
ODOR THRESHOLD: 100 ppm
pH: 6-7
DENSITY (25°C): 0.7866 g/mL
MELTING POINT: -137°F (-94°C)
SOLUBILITY IN WATER: Soluble
VAPOR PRESSURE: 97.25 mm HG @ 20°C
FLASH POINT (cc): 12°C (54°F)
VAPOR DENSITY: 1.11
SOLUBILITY: Soluble in alcohol, acetone, chloroform, ethanol, ether, benzene

Buffer Solutions:

DESCRIPTION: Clear, colorless, odorless liquid
BOILING POINT: 100° C
SPECIFIC GRAVITY: essentially like water
VAPOR PRESSURE: essentially like water
pH: Cat. Numbers 161-6003-0, 161-6004-0 = 7.15
Cat. Numbers 161-6005-0, 161-6006-0 = 6.8
MELTING POINT: essentially like water
SOLUBILITY IN WATER: complete
FLASHPOINT: N/A

10. PHYSICAL AND CHEMICAL PROPERTIES

Wright Stain:

REACTIVITY: Stable under normal temperatures and pressures.
INCOMPATIBILITIES - METHYL ALCOHOL (METHANOL):

ACETYL BROMIDE:	Violent reaction with formation of hydrogen bromide
ALKYLALUMINUM SOLUTIONS:	Violent reaction
ALUMINUM:	Corrodes
BARIUM PERCHLORATE:	Distillation yields highly explosive alkyl perchlorate
BERYLLIUM HYDRIDE:	Violent reaction even at -196°C
BROMIDE:	Vigorously exothermic reaction
CALCIUM CARBIDE:	Violent reaction
CHLORINE:	Possible ignition and explosive hazard
CHLOROFORM AND SODIUM HYDROXIDE:	Explosive reaction
CHROMIUM TRIOXIDE (CHROMIC ANHYDRIDE):	Possible ignition

CYANURIC CHLORIDE:	Violent reaction
DICHLOROMETHANE:	Possible ignition and explosion
DIETHYL ZINC:	Possible ignition and explosion
HYDROGEN PEROXIDE + WATER:	Explosion hazard
IODINE + ETHANOL + MERCURIC OXIDE:	Explosion hazard
LEAD:	Corrodes
LEAD PERCHLORATE:	Explosion hazard
MAGNESIUM:	Violent reaction
MAGNESIUM (POWDER):	Mixtures are capable of detonation
METALS:	Incompatible
NICKEL:	Possible ignition in the presence of nickel catalyst.
NITRIC ACID (CONCENTRATED):	Mixture of greater than 25% acid may decompose violently.
OXIDIZERS (STRONG):	Fire and explosion hazard
PERCHLORIC ACID:	Explosion hazard
PHOSPHOROUS TRIOXIDE:	Possible violent reaction and ignition
PLASTICS, RUBBER, COATINGS:	May be attacked
POTASSIUM:	Possible dangerous reaction
POTASSIUM HYDROXIDE + CHLOROFORM:	Exothermic reaction
POTASSIUM TERT- BUTOXIDE:	Fire and explosion hazard
SODIUM + CHLOROFORM:	Possible explosion
SODIUM HYPOCHLORITE:	Explosion hazard
SODIUM METHOXIDE + CHLOROFORM:	Violent reaction
SULFURIC ACID:	Fire and explosion hazard
ZINC:	Explosion hazard

DECOMPOSITION: Thermal decomposition products may include toxic oxides of carbon.

POLYMERIZATION: Hazardous polymerization has not been reported to occur under normal temperatures and pressures.

Buffer Solutions:

REACTIVITY: Stable under normal temperatures and pressures

INCOMPATIBILITIES: Avoid contact with the following: Oxidizing agents, reducing agents, amines, mercaptants.

DECOMPOSITION: Thermal decomposition may yield the following: Hydrogen chloride, sulfur dioxide, oxides of nitrogen.

POLYMERIZATION: Product will not undergo polymerization

11. TOXICOLOGICAL INFORMATION

100% METHYL ALCOHOL (METHANOL):
skn-rbt 500mg/24H MOD
eye-rbt 40mg MOD
orl-rat LD50: 5627mg/kg
Inh-rat LC50: 64000ppm/4H
orl-man TDLo: 3429mg/kg: EYE
orl-hmn LDLo: 428mg/kg: EYE, PUL
orl-hmn LDLo: 4g/kg: EYE, PUL, GIT
inh-hmn TCLo: 300ppm: EYE, CNS, PUL

12. ECOLOGICAL INFORMATION

Acute toxic effects of Methyl alcohol may include death of animals, birds, or fish and death or low growth rate in plants. Acute effects are seen two to four days after animals or plants come into contact with a toxic chemical substance. Chronic effects may include shortened lifespan, reproductive problems, lower fertility, and changes in appearance or behavior. Chronic effects can be seen long after first exposure(s) to a toxic chemical. Methyl Alcohol has slightly acute and chronic toxic effects to aquatic life. It has caused germination and size decrease and other injury to agricultural and ornamental crops.

13. DISPOSAL GUIDELINES

RCRA: The unused product is a RCRA hazardous waste if discarded; the RCRA ID number is U154/D001. If the waste is a spent solvent, the appropriate solvent code should be used.

DISPOSAL MUST BE IN ACCORDANCE WITH STANDARD APPLICABLE TO GENERATORS OF HAZARDOUS WASTE, 40 CFR 262.

OTHER DISPOSAL CONSIDERATIONS: The waste material should be treated and/or disposed of at a site authorized to handle hazardous chemical waste. Appropriate federal, state and local regulatory authorities should be contacted before discharge, treatment or disposal of waste material. The information offered here is for the product as shipped. Use and alterations to the product such as mixing with other materials may significantly change the characteristics of the material and alter the RCRA classification and the proper disposal method.

14. TRANSPORT INFORMATION

Proper shipping name: Methyl Alcohol Solutions
Hazardous class or Division: 3
Identification Numbers: UN1230
Packaging Group: II
Label(s) Required (if not excepted): Flammable Liquid

15. REGULATORY INFORMATION

SARA TITLE III (Superfund Amendment and Reauthorization Act)

SECTION 302 AND 304: Extremely hazardous substance list (40 CFR 355) - Not listed

SECTION 311: Hazardous Categorization (40 CFR 370) - Acute, Chronic and Fire

SECTION 313: Toxic Chemicals Listed (40 CFR 372.65) - Listed as a toxic chemical

CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)

SECTION 102 (A): Hazardous Substance (40 CFR 302.4) - Listed

REPORTABLE QUANTITIES: 5,000 lbs.

SECTION 101(4): Reportable Quantities: 5,000 lbs.

RCRA (Resource Conservation and Recovery Act)

40 CFR 261.21 Hazardous Waste Number: U154/D001

NJ (New Jersey - State Right to Know)

Environmental Hazardous Substance List: Listed, Substance #1222

TSCA (Toxic Substance Control Act)

Methanol is listed on TSCA Inventory.

16. OTHER INFORMATION:

Sysmex SAS-100, as manufactured by Richard-Allan Scientific, is intended for legal use in laboratories and manufacturing environments.

Sysmex America, Inc. provides the information contained herein in good faith, but makes no representative claim or warranty as to its completeness or accuracy. This document is intended only as a guide for appropriate handling of the material described by properly trained persons using the product according to its intended purposes. Individuals receiving this information retain the responsibility for determining the suitability of the information for any specific purposes. Users should consider these data only as supplement to other information gathered by themselves, and must make independent determinations of the suitability and completeness of information from all sources to ensure proper use and disposal of these materials, and for the safety and health of employees and customers. No warranty, expressed or implied, is made with regard to such information.

Permission is granted to make unlimited copies of this MSDS for internal purposes only.

Revised September 2007